OSRAM GW KAFJB9.KM


Datasheet

Published by ams-OSRAM AG
Tobelbader Strasse 30, 8141 Premstaetten, Austria
Phone +43 3136 500-0
ams-osram.com
© All rights reserved

SOLERIQ™ S 9

GW KAFJB9.KM

The SOLERIQ™ S products were specifically designed for applications requiring large flux packages out of a compact area.



Applications

- Indoor Lighting

Features

- Package: Chip-on-Board
- Typ. Radiation: 120° (Lambertian emitter)
- Color temperature: 2700K - 6500K
- CRI: 90 (min.)
- ESD: 2 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)
- Luminous Flux : typ. 2035 lm @ 3000 K, 85 °C
- Luminous efficacy : typ. 166 lm/W @ 3000 K, 85 °C

Ordering Information

Type	Color temperature	Luminous Flux [1] I_F = 360 mA Φ_V	Ordering Code
GW KAFJB9.KM-D14-27S3	2700 K	1760 ... 2085 lm	Q65115A1879
GW KAFJB9.KM-D15-30S3	3000 K	1850 ... 2195 lm	Q65115A1903
GW KAFJB9.KM-D22-35S3	3500 K	1925 ... 2280 lm	Q65115A1898
GW KAFJB9.KM-D16-40S3	4000 K	1905 ... 2260 lm	Q65115A1902
GW KAFJB9.KM-D17-50S3	5000 K	1915 ... 2270 lm	Q65115A1905
GW KAFJB9.KM-D23-57S3	5700 K	1945 ... 2310 lm	Q65115A1906
GW KAFJB9.KM-D25-65S3	6500 K	1940 ... 2305 lm	Q65115A1907

Maximum Ratings

Parameter	Symbol		Values
Operating Temperature	T_{op}	min. max.	-40 °C 105 °C
Storage Temperature	T_{stg}	min. max.	-40 °C 105 °C
Junction Temperature	T_j	max.	125 °C
Forward Current T_J = 85 °C	I_F	min. max.	40 mA 800 mA
Reverse voltage [2)]	V_R		Not designed for reverse operation
ESD withstand voltage acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)	V_{ESD}		2 kV

Characteristics


I_F = 360 mA; T_J = 85 °C

Parameter	Symbol		Values
Viewing angle at 50% I_V	2φ	typ.	120 °
Forward Voltage [3] I_F = 360 mA	V_F	min. typ. max.	30.00 V 34.00 V 38.00 V
Reverse current [2]	I_R		Not designed for reverse operation
Color Rendering Index [4]	CRI	min.	90
Electrical thermal resistance junction/solderpoint with efficiency η_e = 49.7 %	$R_{thJS\ elec.}$	typ.	0.35 K / W

Brightness Groups

Group	Luminous Flux [1] I_F = 360 mA min. Φ_V	Luminous Flux [1] I_F = 360 mA max. Φ_V
D14	1760 lm	2085 lm
D15	1850 lm	2195 lm
D16	1905 lm	2260 lm
D17	1915 lm	2270 lm
D22	1925 lm	2280 lm
D25	1940 lm	2305 lm
D23	1945 lm	2310 lm

Chromaticity Coordinate Groups [5)]




Chromaticity Coordinate Groups

CCT	Center Cx	Center Cy	a	b	Ø
2700 K	0.4577	0.4098	0.008	0.0041	54.1
3000 K	0.4339	0.4032	0.0086	0.0042	53.7
3500 K	0.4077	0.3929	0.0093	0.0042	53.9
4000 K	0.3818	0.3796	0.0094	0.0041	53.4
5000 K	0.3446	0.3551	0.0081	0.0035	59.8
5700 K	0.3287	0.3425	0.0072	0.0032	58.8
6500 K	0.3123	0.3282	0.0066	0.0027	58.1


Relative Spectral Emission

$\Phi_{rel} = f(\lambda)$; $I_F = 360$ mA; $T_J = 85$ °C




Radiation Characteristics

$I_{rel} = f(\varphi)$; $T_J = 85$ °C




Forward current

$I_F = f(V_F)$; T_J = 85 °C




Relative Luminous Flux

$\Phi_v/\Phi_v(360\ mA) = f(I_F)$; T_J = 85 °C




Chromaticity Coordinate Shift

ΔCx, ΔCy = $f(I_F)$; T_J = 85 °C




Forward Voltage

$\Delta V_F = V_F - V_F(85\ °C) = f(T_j)$; $I_F = 360$ mA




Relative Luminous Flux

$\Phi_v/\Phi_v(85\ °C) = f(T_j)$; $I_F = 360$ mA




Chromaticity Coordinate Shift

$\Delta Cx, \Delta Cy = f(T_j)$; $I_F = 360$ mA




Max. Permissible Forward Current


$I_F = f(T)$



Dimensional Drawing [6)]




Dimensional Drawing [6)]




Tray [6)]

50 pieces per tray



C67062-A0325-X1-02

Barcode-Product-Label (BPL)



OHA04563

Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the device specified in this data sheet fall into the class **moderate risk (exposure time 0.25 s)**. Under real circumstances (for exposure time, conditions of the eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. When looking at bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

This device is designed for specific/recommended applications only. Please consult OSRAM Opto Semiconductors Sales Staff in advance for detailed information on other non-recommended applications (e.g. automotive).

Change management for this component is aligned with the requirements of the lighting market.

For further application related information please visit https://ams-osram.com/support/application-notes

Disclaimer

Attention please!

The information describes the type of component and shall not be considered as assured characteristics.
Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.
For information on the types in question please contact our Sales Organization.
If printed or downloaded, please find the latest version on our website.

Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Product and functional safety devices/applications or medical devices/applications

Our components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.
Our products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using our components in product safety devices/ applications or medical devices/applications, buyer and/or customer has to inform our local sales partner immediately and we and buyer and /or customer will analyze and coordinate the customer-specific request between us and buyer and/or customer.

Glossary

1) **Brightness:** Brightness values are measured during a current pulse of typically 10 ms, with a tolerance of +/- 7%.

2) **Reverse Operation:** Not designed for reverse operation. Continuous reverse operation can cause migration and damage of the device.

3) **Forward Voltage:** The Forward voltage is measured during a current pulse duration of typically 1 ms with a tolerance of ± 0.05V .

4) **Color reproduction index:** Color reproduction index values (CRI-RA) are measured during a current pulse of typically 10 ms and with a tolerance of ±2.

5) **Chromaticity coordinate groups:** Chromaticity coordinate groups are measured during a current pulse duration of typically 10ms with a tolerance of ±0.005.

6) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with ±0.1 and dimensions are specified in mm.

Revision History

Version	Date	Change
1.0	2025-08-11	Initial Version
1.1	2025-10-15	Characteristics Brightness Groups Features
1.2	2025-12-08	Certificate Logo

EU RoHS and China RoHS compliant product
此产品符合欧盟 RoHS 指令的要求；
按照中国的相关法规和标准，
不含有毒有害物质或元素。

Published by ams-OSRAM AG
Tobelbader Strasse 30, 8141 Premstaetten, Austria
Phone +43 3136 500-0
ams-osram.com
© All rights reserved